

IN THE CLAIMS:

Please amend the claims as follows:

---

- A2
1. (Currently Amended) A wireless mobile terminal system comprising:
- a GPS receiver;
  - ~~an~~ a first antenna, coupled to the GPS receiver, for allowing the GPS receiver to receive GPS signals transmitted from at least one GPS satellite;
  - a wireless transceiver;
  - a second antenna, coupled to the transceiver, for allowing the transceiver to transmit signals and further for allowing the transceiver to receive signals;
  - a first coupling means, coupled to the transceiver, for obtaining a replica signal from the transceiver, the replica signal being a replica of a signal being transmitted by the transceiver;
  - a phase and gain adjusting means, with an input coupled to the first coupling means, for accepting and selectively conditioning the replica signal; and
  - a second coupling means, coupled to the output of the phase and gain adjusting means, for providing the selectively phase and gain adjusted replica signal to the GPS receiver, wherein the selectively phase and gain adjusted replica signal reduces interference between a transmitted signal from the transceiver and a signal received by the GPS receiver.

2. (Currently Amended) The ~~GPS-receiver~~ system of claim 1, wherein the first antenna and the second antenna comprise ~~are~~ a single antenna.

3. (Currently Amended) The ~~GPS-receiver~~ system of claim 1 2, wherein the phase and gain adjusting means uses a feedback loop to reduce the interference between the transmitted signal from the transceiver and the signal received by the GPS receiver.

4 - 6. (Canceled)

A2  
7. (Currently Amended) The ~~GPS-receiver~~ system of claim 3 6, wherein the ~~phase shift of the transmitted signal and the amplitude shift of the transmitted signal are controlled by~~ feedback loop comprises a received signal strength indicator for controlling adjustment of the phase and gain of the replica signal.

8. (Currently Amended) The ~~GPS-receiver~~ system of claim 3 7, wherein the feedback loop combining circuit further comprises an adaptive circuit.

9. (Currently Amended) The ~~GPS-receiver~~ system of claim 8, wherein the adaptive circuit minimizes long-term drift effects.

(10.) (Original) A method for reducing interference in a Global Positioning System (GPS) receiver that shares an antenna with a transceiver, comprising the steps of:

replicating a first transmission of the transceiver, wherein the first transmission of the receiver emanates from an antenna receiving GPS signals;  
coupling the replicated transmission into a front end of the GPS receiver; and  
at least partially canceling the first transmission using the replicated transmission.

11. (Currently Amended) The method of claim 10, wherein the at least partial cancellation is performed using a feedback loop.

12. (Canceled)

A2  
13. (Currently Amended) The method of claim 10 12, further comprising phase shifting the replicated transmission signal.

14. (Currently Amended) The method of claim 13, further comprising amplitude shifting the replicated transmission signal.

15. (Currently Amended) The method of claim 14, further comprising controlling the phase shifting of the replicated transmission signal and the amplitude shifting of the replicated transmission signal by using a received signal strength indicator.

16. (Currently Amended) The method of claim 10 15, further comprising minimizing long-term drift effects.

17. (Original) The method of claim 16, wherein the minimizing of long-term drift effects is performed by an adaptive circuit.

Please add the following new claims 18-24:

18. (New) The method of claim 10 comprising amplitude shifting the replicated transmission.

A2

19.

(New) A wireless communication system comprising:

- (a) a wireless transceiver for receiving and transmitting communication signals;
- (b) a GPS receiver for receiving GPS signals; and
- (c) a feedback circuit for receiving a replica signal from the transceiver, the replica signal being a replica of a signal transmitted by the transceiver, for conditioning the replica signal, and for providing the conditioned replica signal to the GPS receiver as an interference cancellation signal.

20. (New) The system of claim 19 wherein the feedback circuit comprises a gain adjusting component for adjusting the gain of the replica signal.

21. (New) The system of claim 20 wherein the feedback circuit comprises a phase adjusting component for adjusting the phase of the replica signal.

22. (New) The system of claim 21 wherein the feedback circuit comprises a receive signal strength indicator for controlling the gain adjusting component and the phase adjusting component.

*Ad  
enclosed*  
23. (New) The system of claim 19 wherein the feedback circuit comprises a phase adjusting component for adjusting the phase of the replica signal.

24. (New) The system of claim 19 wherein the feedback circuit comprises a receive signal strength indicator for conditioning the replica signal.

---